

Asphalt Crack Filler

Watco Asphalt Crack Filler is a polymer modified flexible crack filler for asphalt, tarmac and all bituminous surfaces.



Unsightly cracks in asphalt can lead to water ingress, erosion and accelerated deterioration of the surface. This rubberised bitumen based product makes crack repairs easy. Simply decant the liquid into a spouted can and pour into the crack.



Areas of use:

- Car parks
- Walkways
- School playgrounds
- Tarmac and Asphalt Surfaces

Features:

- Flexible to allow for expansion and movement
- Ideal for cracks up to 3mm
- Cracks 3mm - 25mm can be filled by mixing Watco Asphalt Crack Filler with Watco Sand Additive
- Long lasting protection against ingress of water
- Can be overcoated with Watco Black Top or Watco Asphalt Restorer if required
- Excellent adhesion

Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Asphalt Crack Filler**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



Asphalt Crack Filler

1 Surface Preparation

Sweep or scrape out loose debris from the crack.

2 Mixing

Stir well before use.

3 Application

Do not use in wet or cold (below 5°C) conditions. Damp or cold weather will delay the drying time. The crack should be reasonably dry, although a little dampness may be tolerated.

Cracks up to 3mm wide – Pour the Watco Asphalt Crack Filler into the cracks using a spouted can (available from Watco). Alternatively a watering can may be used.

Brush out to a thin film any surplus liquid which overflows the edges of the crack.

Once the Watco Asphalt Crack Filler has dried, dust with very fine sand or cement to remove any residual tack.

Cracks 3mm - 25mm wide – Prime the sides of the crack with a brush coat of Watco Asphalt Crack Filler. Mix Watco Asphalt Crack Filler with damp sand (Watco Sand Additive is available) to produce a slightly stiff mortar. Trowel into the crack and smooth off. Once the mortar is dry, dust with very fine sand or cement to remove any residual tack.

4 Safety

All product labels provide general safety information. Material Safety Data Sheets are available. Food products must be removed from the area during application and cure.

5 Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

Asphalt Crack Filler

Specification

Composition	Rubberised black bitumen emulsion.
Number of Components	1
Usage Interior/Exterior	Exterior & interior.
Application Tools	Spouted can.
Suitable For	Asphalt, tarmac.
Pack Size	5L
Coverage	5 litres will fill 100 linear metres of cracks at 5mm wide & 5mm deep
Drying Time	Approximately 2 - 4 hours should be allowed for cracks up to 3mm and 6 -10 hours for cracks up to 25mm.
Cleaning Tools	Use water and detergent if the product has not dried. Once dried, use white spirit.
Shelf Life	12 months in unopened container.
Storage	Protect from frost and direct sunlight. Do not allow to freeze.
Principle Limitations	This product is designed for use on bitumen based surfaces. It could soften surfaces which contain coal tar. If in doubt, apply a test area and check after 24 hours that no softening has occurred.
Please contact us regarding applications not described here.	